



## GLADIO SMALL BORE

### ANCIENT ROOTS.

Our tribute to the weapon of the ancient Rome that conquered the world known until then wears today a brand-new look: Victrix Small Bore breaks through the borders and conquer new and uncharted territories.

 **VICTRIX**  
A R M A M E N T S

**Destination use**

Sporting  
Military training

**Caliber / Twist rate**

.22 L.R. (1/16)

**Barrel length**

22"  
24"  
26"

**Weight**

5,95 kg (13.12 lb) with an empty magazine, barrel length 22" and no scope  
6,08 kg (13.40 lb) with an empty magazine, barrel length 24" and no scope  
6,20 kg (13.67 lb) with an empty magazine, barrel length 26" and no scope

**Dimension**

Closed overall length: 804 mm (31.65")  
Open overall length: 1050 mm (41.33")  
With muzzle thread protector and barrel length 22"

Closed overall length: 854 mm (33.62")  
Open overall length: 1100 mm (43.30")  
With muzzle thread protector and barrel length 24"

Closed overall length: 906 mm (35.66")  
Open overall length: 1152 mm (45.35")  
With muzzle thread protector and barrel length 26"



**Base rifle**

Barrel in special steel  
Buttstock with horizontal and vertical multiple lever adjustments, a retractable monopod with quick positioning adjustment and fine adjustment, and an insulated cheek piece  
Single feed and single stack 10-round magazine  
Reversible EVO button folding system  
Octagonal elliptic forend with attachment system for accessories, a 20 MoA integrated monobloc top rail and an integrated monobloc rail for mounting a bipod according to STANAG 4694/Mil std 1913  
Ergonomic and interchangeable zero angle flat top grip for standard AR platform  
20 MoA removable action rail according to STANAG 4694/Mil std 1913  
Muzzle thread protector  
Detachable multifunction carry handle with quick mount:  
· With QM (Quick mount) attachment for picatinny rail  
· Ergonomic handle  
· Integrated picatinny rail  
· Hook for rope attachment  
· QD (Quick detach) attachments  
· Tripod attachment with 1/4" – 20 UNC and 3/8" – 16 UNC threads  
· Front magnetic bit holder for field maintenance  
Action in AISI 630 worked out from billet  
Bolt with two asymmetric rear lugs arranged at an angle of 60-degree lift, with a quick disassembly system, a double extractor and an ergonomic interchangeable bolt lever  
PVD finish on the action and on the bolt  
Victrix Sporting Plus adjustable single stage trigger with a two-position safety: standard setting approx. 250 gr (8.82 oz)  
Heavy-duty reinforced transport case  
User manual and welcome kit

**Stock colour**

CERAKOTE ceramic polymer firearm coatings available in:  
Dark Grey  
Dark Olive Drab Green  
Medium Flat Brown  
Graphite Black

**Optional**

Side picatinny rails for forend with attachment system for accessories according to STANAG 4694/Mil std 1913  
45 MoA action rail according to STANAG 4694/Mil std 1913

*In case of discrepancy between the data contained in the technical specification and what is visible from the photos, the information reported in the data sheet published on the official website shall prevail.*

