



## GLADIO V

### FIELD-TESTED, FROM 2.400 YEARS.

From the last legionary to the most important centurion, all of them had a Gladio.

Our roots are based in the history of a state that became an empire. The Victrix Gladio is our tribute to the main weapon of ancient Rome.

 **VICTRIX**  
A R M A M E N T S

**Destination use**

Law Enforcement  
 Military  
 Sporting

**Caliber / Twist rate**

.308 Win. (1/10 – 1/11)  
 .308 Match (1/10 – 1/11)  
 .260 Remington (1/8.5)  
 6,5 Creedmoor (1/8)  
 6,5 Creedmoor (1/8.5)

**Barrel length**

22"  
 26"

**Weight**

6,32 kg (13.93 lb) with an empty magazine, muzzle brake, barrel length 22" and no scope  
 6,62 kg (14.59 lb) with an empty magazine, muzzle brake, barrel length 26" and no scope

**Dimension**

Closed overall length: 868 mm (34.17")  
 Open overall length: 1113 mm (43.82")  
 With muzzle brake and barrel length 22"

Closed overall length: 969 mm (38.15")  
 Open overall length: 1215 mm (47.84")  
 With muzzle brake and barrel length 26"

**Base rifle**

Lapped match-grade button rifled barrel in AISI 416R  
 Buttstock with horizontal and vertical multiple lever adjustments, a retractable monopod with quick positioning adjustment and fine adjustment, and an insulated cheek piece  
 Single feed and double stack 10-round metal magazine  
 Reversible EVO button folding system  
 Octagonal elliptical forend with attachment system for accessories, a 20 MoA integrated monobloc top rail and an integrated monobloc rail for mounting a bipod according to STANAG 4694/Mil std 1913  
 Ergonomic and interchangeable zero angle flat top grip for standard AR platform  
 20 MoA action rail according to STANAG 4694/Mil std 1913  
 Detachable multifunction carry handle with quick mount:  
 · With QM (Quick mount) attachment for picatinny rail  
 · Ergonomic handle  
 · Integrated picatinny rail  
 · Hook for rope attachment  
 · QD (Quick detach) attachments  
 · Tripod attachment with 1/4" – 20 UNC and 3/8" – 16 UNC threads  
 · Front magnetic bit holder for field maintenance  
 Victrix ProAngle detachable muzzle brake featuring 3 forward canted chambers  
 Short action in AISI 630 worked out from billet through milling and turning with finish on electro-discharge and grinding machinery.  
 Bolt with three asymmetric lugs: first lug on top of the cylinder in vertical position (at 12 o'clock), two side lugs arranged at an angle of 105-degree lift, dirt/ice grooves integral and an ergonomic interchangeable bolt lever  
 PVD finish on the action and on the bolt  
 Victrix Professional dual stage trigger, convertible to a single stage trigger, with two positions top safety: standard setting approx. 1000 gr (35.27 oz)  
 Heavy-duty reinforced transport case  
 User manual and welcome kit

**Stock colour**

CERAKOTE ceramic polymer firearm coatings available in:  
 Dark Grey  
 Dark Olive Drab Green  
 Medium Flat Brown  
 Graphite Black

**Optional**

Side picatinny rails for forend with attachment system for accessories according to STANAG 4694/Mil std 1913

*In case of discrepancy between the data contained in the technical specification and what is visible from the photos, the information reported in the data sheet published on the official website shall prevail.*



VICTRIX  
 PROFESSIONAL