

# ORB SMALL BORE

## THE CORONATION.

Orb Small Bore, the youngest member of our Victrix Armaments ELR royal family is finally available. Everything is ready for the coronation, let the ceremony begin.





#### **Destination use**

.22 L.R. shooting

**Caliber / Twist rate** .22 L.R. (1/16)

### **Barrel length**

22″

#### Weight

6.65 kg (14.66 lb), with an empty magazine, a muzzle thread protector and no scope

#### Dimension

Closed overall length: 804 mm (31.65") Open overall length: 1063 mm (41.85") With muzzle thread protector and barrel length 22"

#### **Base rifle**

Special steel rifled barrel with a bull barrel contour Buttstock with a horizontal and vertical adjustment, and an insulated cheek piece Rear slider inclined at 3 degrees, vertically adjustable by ring Single feed and single stack 10-round polymer magazine Reversible EVO button folding system High strength monobloc chassis in light alloy ready to mount accessories or hold ammunition, and an ergonomic thumb rest Light profile forend in light alloy equipped with an integrated Anschutz-type rail in the middle and an integrated Arca rail that run the entire length and a side system to mount accessories Handguard cover on the front with Picatinny rail L=172,5 mm (6.79") Wider trigger guard Ergonomic and interchangeable zero angle flat top grip for standard AR platform Muzzle thread protector Action in AISI 630 worked out from billet with a 20 MoA removable rail in light alloy Bolt with two asymmetric rear lugs arranged at an angle of 60-degree lift, with a quick disassembly system, a double extractor and an ergonomic interchangeable bolt lever PVD finish on the action and on the bolt Victrix Sporting Plus adjustable single stage trigger with a two-position safety: standard setting approx. 250 gr (8.82 oz) Heavy-duty reinforced transport case User manual and welcome kit

#### Stock colour

CERAKOTE ceramic polymer firearm coating available in: Burnt Bronze

#### Optional

45 MoA action rail in light alloy Handguard cover on the front with Picatinny rail L=296 mm (11.65")

In case of discrepancy between the data contained in the technical specification and what is visible from the photos, the information reported in the data sheet published on the official website shall prevail.



