



TARGET SMALL BORE

THE FUTURE IS IN THE SMALL THINGS.

The new stock of the Target SB is also made of structural T1000 carbon, which is the first stock in the world in carbon fiber with non-homogeneous zones. In order to guarantee different functions, in different areas. Even in .22 LR caliber.

 **VICTRIX**
A R M A M E N T S



TARGET SB

DATA SHEET

Destination use

Sporting by bipod

Caliber / Twist rate

.22 L.R. (1/16)

.22 L.R. (1/7) Ideal for ammunition reloaded with solid bullets

.22 L.R. (1/10) Ideal for ammunition reloaded with solid bullets

Barrel length

24"

24" with a threaded muzzle

27"

27" with a threaded muzzle

Weight

5,37 kg (11.84 lb) with barrel length 24" and no scope

5,38 kg (11.86 lb) with barrel length 24", muzzle thread protector and no scope

5,67 kg (12.50 lb) with barrel length 27" and no scope

5,68 kg (12.52 lb) with barrel length 27", muzzle thread protector and no scope

Dimension

Closed overall length: 1093 mm (43.03")

Open overall length: 1133 mm (44.60")

With barrel length 24"

Closed overall length: 1169 mm (46.02")

Open overall length: 1209 mm (47.59")

With barrel length 27"

Base rifle

Barrel in special steel, muzzle at 1"

Stock made of a special T1000 carbon fiber, equipped with a rib that

enhances its rigidity and reduces the normal torsion when shooting

Cutting-edge rear slider inclined at 3 degrees in length to offer the shooter the best comfort

Integrated rubber buttpad with horizontal and vertical button adjustments

Carbon fiber adjustable cheek-piece

Anschutz-type rail in light alloy for mounting a bipod

Muzzle thread protector (where provided)

Anima® system, stock with a monolithic bedding in light alloy

Single-shot action in AISI 630 worked out from billet with a 20 MoA removable rail in light alloy

Bolt with two asymmetric rear lugs arranged at an angle of 60-degree lift, with a quick disassembly system, a double extractor and

an ergonomic interchangeable bolt lever

PVD finish on the action and on the bolt

Victrix Sporting V adjustable single stage trigger: standard setting

approx. 40 gr (1.41 oz)

Heavy-duty reinforced transport case

User manual and welcome kit

Stock colour

Visible carbon fiber

In case of discrepancy between the data contained in the technical specification and what is visible from the photos, the information reported in the data sheet published on the official website shall prevail.

Visible carbon fiber



VICTRIX
SMALL BORE