



TARGET V

THE FIRST, THE MOST SUCCESSFUL.

Being a forerunner means having a main advantage: time. Our Victrix Target boasts victories in F-Class FTR nationals, worldwide championships, and competitions. Being the first means having a main advantage: time.

 **VICTRIX**
A R M A M E N T S

Destination use

Sporting by bipod

Caliber / Twist rate

.308 Match (1/11 - 30")
 .308 Match (1/10 - 32")
 .308 Match (1/9,5 - 32")
 .300 WSM (1/10 - 32")
 .300 WSM (1/9,5 - 32")
 .308 Win. (1/11 - 30")
 6,5 Creedmoor (1/7,5 - 30")
 6,5×47 Lapua (1/7,5 - 30")
 6,5 Creedmoor (1/8,5 - 30")
 6,5×47 Lapua (1/8,5 - 30")
 6 XC (1/8,5 - 28")
 6 BR (1/8,5 - 28")

Barrel length

See section Caliber

Weight

6,03kg (13.29 lb) no scope, barrel length 28"
 6,20 kg (13.67 lb) no scope, barrel length 30"
 6,41 kg (14.13 lb) no scope, barrel length 32"

Dimension

Closed overall length: 1206 mm (47.48")
 Open overall length: 1246 mm (49.05")
 With barrel length 28"

Closed overall length: 1256 mm (49.44")
 Open overall length: 1296 mm (51.02")
 With barrel length 30"

Closed overall length: 1307 mm (51.45")
 Open overall length: 1347 mm (53.03")
 With barrel length 32"

Base rifle

Lapped button rifled barrel in AISI 416R, muzzle at 1"
 Stock made of a special T1000 carbon fiber, equipped with a rib that enhances its rigidity and reduces the normal torsion when shooting
 Cutting-edge rear slider inclined at 3 degrees in length to offer the shooter the best comfort
 Integrated rubber butt pad with horizontal and vertical button adjustments
 Carbon fiber adjustable cheek-piece
 Anima® system, stock with a monolithic bedding in light alloy
 20 MoA removable action rail in light alloy
 Anschutz-type rail in light alloy for mounting a bipod
 Single-shot action in AISI 630 worked out from billet through milling and turning with finish on electro-discharge and grinding machinery.
 Bolt with three asymmetric lugs: first lug on top of the cylinder in vertical position (at 12 o'clock), two side lugs arranged at an angle of 105-degree lift and an interchangeable lever in light alloy
 PVD finish on the action and on the bolt
 Victrix Sporting V Adjustable single stage trigger: standard setting approx. 60 gr (2.12 oz)
 Heavy-duty reinforced transport case
 User manual and welcome kit

Stock colour

Visible carbon fiber

In case of discrepancy between the data contained in the technical specification and what is visible from the photos, the information reported in the data sheet published on the official website shall prevail.

Visible carbon fiber



VICTRIX
SPORTING