



## CORVO V

### A SNIPER RIFLE, IN .50 BMG.

We've designed Corvo to have more control over the extreme power, holding our accuracy flag high. To give you an idea, think about the accuracy of a sniper firearm system together with the energy of a .50 BMG caliber.

 **VICTRIX**  
A R M A M E N T S

**Destination use**

Law Enforcement  
Military

**Caliber / Twist rate**

.50 BMG (12,7x99) (1/15)

**Barrel length**

27"

**Weight**

13.2 kg (29.10 lb) with an empty magazine, muzzle brake, fluted barrel length 27" and no scope

**Dimension**

Closed overall length: 1175 mm (46.22")

Open overall length: 1420 mm (56.14")

With muzzle brake and fluted barrel length 27"

**Base rifle**

Lapped and fluted match-grade rifled barrel in AISI 420  
Buttstock with horizontal and vertical multiple lever adjustments, a retractable monopod with quick positioning adjustment and fine adjustment, and an insulated cheek piece  
Single feed and single stack 5-round magazine  
Reversible EVO button folding system  
Octagonal elliptic forend with attachment system for accessories, a 45 MoA integrated monobloc top rail and an integrated monobloc rail for mounting a bipod according to STANAG 4694/Mil std 1913  
Ergonomic and interchangeable zero angle flat top grip for standard AR platform  
45 MoA action rail according to STANAG 4694/Mil std 1913  
Detachable multifunction carry handle with quick mount:  
· With QM (Quick mount) attachment for picatinny rail  
· Ergonomic handle  
· Integrated picatinny rail  
· Hook for rope attachment  
· QD (Quick detach) attachments  
· Tripod attachment with 1/4" – 20 UNC and 3/8" – 16 UNC threads  
· Front magnetic bit holder for field maintenance  
Victrix ProAngle detachable muzzle brake featuring 4 forward canted chambers  
Action in AISI 420 worked out from billet through milling and turning with finish on grinding machinery. Bolt with 3 symmetric lugs: first lug at the bottom of the cylinder in vertical position (at 6 o'clock), two side lugs arranged at an angle of 120-degree, dirt/ice grooves integral  
PVD finish on the action and on the bolt  
Victrix Professional Plus trigger with three positions top safety: standard setting approx. 1000 gr (35.27 oz)  
Heavy-duty reinforced transport case with military specifications with custom cut interior  
Cleaning and tool kit with cordura pouch  
Nr. 1 additional single feed and single stack 5-round magazine  
Tactical sling and QD (Quick Detach) sling rings  
ROME Caliga bipod  
User manual and welcome kit

**Stock colour**

CERAKOTE ceramic polymer firearm coatings available in:  
Dark Grey  
Dark Olive Drab Green  
Medium Flat Brown

**Optional**

Side picatinny rails for forend with attachment system for accessories according to STANAG 4694/Mil std 1913

*In case of discrepancy between the data contained in the technical specification and what is visible from the photos, the information reported in the data sheet published on the official website shall prevail.*

