

PERFORMANCE V

WHAT'S YOUR NEXT LEVEL?

Find it out with Victrix Performance. Its aluminium chassis will let you savour every step hard-won. A pleasure never experienced before will make you feel truly at one with your Victrix system. Take the time to get used to her but be careful, there's no room for error





Destination use

Sporting by bipod / rest

Caliber / Twist rate

.308 Match (1/11 - 30") .308 Match (1/10 - 32") .308 Match (1/9,5 - 32") .300 WSM (1/10 - 32") .300 WSM (1/9,5 - 32") .308 Win. (1/11 - 30") 6,5 Creedmoor (1/8,5 - 30") 6,5×47 Lapua (1/8,5 - 30") 6 XC (1/8,5 - 28")

Barrel length

6 BR (1/8,5 - 28")

See section Caliber

Weight

6,40 kg (14.10 lb) no scope, barrel length 28" 6,60 kg (14.55 lb) no scope, barrel length 30" 6,80 kg (14.99 lb) no scope, barrel length 32"

Dimension

Overall length 1200 mm (47.24") With barrel length 28"

Overall length 1250 mm (49.21") With barrel length 30"

Overall length 1300 mm (51.18") With barrel length 32"

Base rifle

Lapped button rifled barrel in AISI 416R, muzzle at 1" Buttstock with a horizontal and vertical adjustment, and an insulated cheek piece

Ergonomic and interchangeable zero angle flat top grip standard AR platform

High strength monobloc chassis in light alloy

Light profile forend with reinforcement points to achieve an overall rigidity, with an integrated Anschutz-type rail for mounting a bipod 20 MoA action rail in light alloy

Single-shot action in AISI 630 worked out from billet through milling and turning with finish on electro-discharge and grinding machinery. Bolt with three asymmetric lugs: first lug on top of the cylinder in vertical position (at 12 o'clock), two side lugs arranged at an angle of 105-degree lift, and an ergonomic interchangeable bolt lever

PVD finish on the action and on the bolt Victrix Sporting V adjustable single stage trigger: standard setting approx. 60 gr (2.12 oz)

Heavy-duty reinforced transport case User manual and welcome kit

Stock colour

CERAKOTE ceramic polymer firearm coating available in: Medium Light Grey

In case of discrepancy between the data contained in the technical specification and what is visible from the photos, the information reported in the data sheet published on the official website shall prevail.

Medium Light-Grey



