

SCEPTER SMALL BORE

A SMALL SCEPTER FOR A GREAT KING!

Our royal family is growing: Scepter Small Bore is the new frontier of .22 ELR shooting, it's a small scepter that will make of you a great king.





Destination use

Precision sport shooting

Caliber / Twist rate

.22 L.R. (1/16) .22 L.R. (1/7) Ideal for ammunition reloaded with solid bullets .22 L.R. (1/10) Ideal for ammunition reloaded with solid bullets

Barrel length

24"24" with a threaded muzzle27"27" with a threaded muzzle

Weight

6,30 kg (13.89 lb) with barrel length 24" and no scope 6,29 kg (13.87 lb) with barrel length 24", muzzle thread protector and no scope 6,60 kg (14.55 lb) with barrel length 27" and no scope 6,59 kg (14.53 lb) with barrel length 27", muzzle thread protector and no scope The weight may vary of +/- 100 gr (3.53 oz) depending on the origin of the raw material

Dimension

Overall length 1083 mm (42.64") With barrel length 24"

Overall length 1160 mm (45.67") With barrel length 27"

Barrel in special steel Buttstock with a horizontal and vertical adjustment, and an insulated cheek piece Rear slider inclined at 3 degrees, vertically adjustable by ring Reversible EVO button folding system Ergonomic and interchangeable zero angle flat top grip standard AR platform High strength monobloc chassis in light alloy Light profile forend with reinforcement points to achieve an overall rigidity, with an integrated Anschutz-type rail for mounting a bipod Muzzle thread protector (where provided) Single-shot action in AISI 630 worked out from billet with a 20 MoA removable rail in light alloy Bolt with two asymmetric rear lugs arranged at an angle of 60-degree lift, with a quick disassembly system, a double extractor and an ergonomic interchangeable bolt lever PVD finish on the action and on the bolt Victrix Sporting V adjustable single stage trigger: standard setting approx, 40 gr (1,41 oz) Heavy-duty reinforced transport case User manual and welcome kit

Base rifle

Stock colour

CERAKOTE ceramic polymer firearm coating available in: Orobic Blue

Optional

45 MoA action rail in light alloy

In case of discrepancy between the data contained in the technical specification and what is visible from the photos, the information reported in the data sheet published on the official website shall prevail.



