

# THRONE V

# RIGHTFUL HEIRS.

To us, long distances hide few secrets as well as the power struggles within our catalogue. Take your side: Victrix Throne with magazine or Crown single-shot. Same reliability, same concept of precision.





# **Destination use**

**ELR TAC Shooting** 

#### Caliber / Twist rate

.375 CT (1/8) .408 CT (1/10)

# **Barrel length**

38"

## Weight

14,5 kg (31.97 lb) with an empty magazine, muzzle brake, barrel length 38" and no scope

#### Dimension

Closed overall length: 1405 mm (53.31") Open overall length: 1667 mm (65.63") With muzzle brake and barrel length 38"

#### Base rifle

Lapped rifled barrel in AISI 416R

High strength monobloc chassis in light alloy

Buttstock with a horizontal and vertical adjustment, and an insulated cheek piece

Rear slider inclined at 3 degrees, vertically adjustable by a gold finished ring

Single feed and single stack 7-round polymer magazine High strength EVO folding system in light alloy Ergonomic and interchangeable grip with palm shelf 45 MoA action rail in special steel

Anschutz-type bottom rail for mounting a bipod

Victrix ProAngle detachable muzzle brake featuring 3 forward canted chambers

Action in AISI 420 worked out from billet through milling and turning with finish on grinding machinery. Bolt with 3 symmetric lugs: first lug at the bottom of the cylinder in vertical position (at 6 o'clock), two side lugs arranged at an angle of 120-degree PVD finish on the action and on the bolt

Victrix Sporting Plus trigger with two positions top safety and a gold finish on the trigger lever: standard setting approx. 500 gr (17.64 oz)

Muzzle thread protector Heavy-duty reinforced transport case User manual and welcome kit

#### Stock colour

CERAKOTE ceramic polymer firearm coating available in: Medium Dark Grey with Silver Metallic

# **Optional**

Anschutz-type to picatinny accessory rail with quick detach attachments

In case of discrepancy between the data contained in the technical specification and what is visible from the photos, the information reported in the data sheet published on the official website shall prevail.

Medium dark-grey with silver metallic



