



TORMENTO V

WITH EXTREME PRECISION.

Victrix Tormento is the rifle chosen by expert shooters to get to extreme distances. Choose among its two calibers, .375 CT and .408 CT. Get even furthestmost than who believes to get farther.

 **VICTRIX**
A R M A M E N T S

TORMENTO V

DATA SHEET

Destination use

Law Enforcement
Military
Sporting

Caliber / Twist rate

.375 CT (1/10)
.408 CT (1/13)

Barrel length

30"

Weight

11,5 kg (25.35 lb) with an empty magazine, muzzle brake, fluted barrel length 30" and no scope

Dimension

Closed overall length: 1201 mm (47.28")

Open overall length: 1447 mm (56.97")

With muzzle brake and fluted barrel length 30"

Base rifle

Lapped and fluted match-grade button rifled barrel in AISI 416R
Buttstock with horizontal and vertical multiple lever adjustments, a retractable monopod with quick positioning adjustment and fine adjustment, and an insulated cheek piece

Single feed and single stack 7-round polymer magazine

Reversible EVO button folding system

Octagonal elliptic forend with attachment system for accessories, a 45 MoA integrated monobloc top rail and an integrated monobloc rail for mounting a bipod according to STANAG 4694/Mil std 1913
Ergonomic and interchangeable zero angle flat top grip for standard AR platform

45 MoA action rail according to STANAG 4694/Mil std 1913

Detachable multifunction carry handle with quick mount:

- With QM (Quick mount) attachment for picatinny rail
- Ergonomic handle
- Integrated picatinny rail
- Hook for rope attachment
- QD (Quick detach) attachments
- Tripod attachment with 1/4" – 20 UNC and 3/8" – 16 UNC threads
- Front magnetic bit holder for field maintenance

Victrix ProAngle detachable muzzle brake featuring 3 forward canted chambers

Action in AISI 420 worked out from billet through milling and turning with finish on grinding machinery. Bolt with 3 symmetric lugs: first lug at the bottom of the cylinder in vertical position (at 6 o'clock), two side lugs arranged at an angle of 120-degree, dirt/ice grooves integral

PVD finish on the action and on the bolt

Victrix Professional Plus trigger with two positions top safety: standard setting approx. 1000 gr (35.27 oz)

Heavy-duty reinforced transport case

User manual and welcome kit

Stock colour

CERAKOTE ceramic polymer firearm coatings available in:

Dark Grey


Dark Olive Drab Green

Medium Flat Brown

Optional

Side picatinny rails for forend with attachment system for accessories according to STANAG 4694/Mil std 1913

In case of discrepancy between the data contained in the technical specification and what is visible from the photos, the information reported in the data sheet published on the official website shall prevail.



VICTRIX
PROFESSIONAL